

Brass / Bronze Safety Relief Valve - Angle Pattern

Flanged PN16, Metal Seat

Pressure / Temperature Specifications	
Pressure	PN16 ½" to 2"
	PN10 2½" to 4"
Temperature	-10°C to 220°C

Material Specifications	
Body	Bronze
Bonnet	Brass
Internals	Brass
Seat	Bronze
Spring	Steel

Dimensions				
DN	H	A	B	Kg
½"	155	60	60	1.7
¾"	183	65	65	2.2
1"	202	72	72	3.2
1¼"	239	85	85	4.8
1½"	255	90	90	6.1
2"	280	105	105	8.5
2½"	320	110	110	12.5
3"	337	115	115	14.5
4"	415	140	140	20.0

Spring Ranges (Bar)				
½"	0.1 - 2	2 - 6		6 - 16
¾"	0.1 - 2	2 - 6		6 - 16
1"	0.1 - 2	2 - 4	4 - 8	8 - 16
1¼"	0.1 - 2	2 - 4	4 - 8	8 - 16
1½"	0.1 - 2	2 - 4	4 - 8	8 - 16
2"	0.1 - 2	2 - 4	4 - 8	8 - 16
2½"	0.1 - 2			2 - 10
3"	0.1 - 2			2 - 10
4"	1.5 - 3.5			5 - 10

