

Brass Spring Check Valve + Strainer

LV 2290

Screwed **BSPP**, Brass Body, Acetal Disc, NBR Seat, with Fixed Stainless Steel Filter.

Pressure / Temperature Specifications	
Pressure	½" to 1" PN10
	1¼" to 2" PN8
	2½" & 4" PN6
Temperature	0°C to 95°C (-20°C to 110°C Peak)

Material Specifications	
1. Body	Brass UNI EN 12165 CW617N
2. Disc	POM
3. Washers	NBR
4. Spring	Stainless Steel AISI 302
5. Filter Fitting	Nylon
6. Filter	Stainless Steel AISI 304 L

Dimensions							
G	D	H	A	F	B	X	Kg
½"	29	80	1.1mm²	850µm	2.6	24	0.08
¾"	37	90	1.1mm²	850µm	2.6	24	0.12
1"	44	100	1.1mm²	850µm	2.6	24	0.17
1¼"	56	110	1.1mm²	850µm	2.6	24	0.27
1½"	63	126	1.1mm²	850µm	2.6	24	0.33
2"	78	146	1.1mm²	850µm	2.6	24	0.54
2½"	103	162	1.1mm²	850µm	2.6	24	1.0
3"	120	188	1.1mm²	850µm	2.6	24	1.54
4"	155	214	1.1mm²	850µm	2.6	24	2.62

