

Brass Pressure Reducing Valve - PN25

BSPP Male Union Ends, Brass Body, EPDM O-rings & Gaskets, Built-in Stainless Steel Filter, Adjustable Outlet Pressure between 1.5 and 6 Bar, Maximum Inlet Pressure 25 Bar, with Gauge Port



Pressure / Temperature Specifications	
Pressure	PN25
Temperature	0°C to 80°C

Material Specifications			
1. Body	CW617N Brass	16. Nut	Stainless Steel
2. Bonnet	CW617N Brass	17. Disc	POM
3. O-ring	EPDM	18. Spring	Stainless Steel
4. Filter	Stainless Steel & POM	19. Spacer	CW617N Brass
5. Gasket	EPDM	20. Stem	CW617N Brass
6. Insert	POM	21. Cover	Nylon
7. Stem	CW617N Brass	22. Ring	POM
8. Insert	POM	23. Handle	Nylon
9. O-ring	EPDM	24. Screw	CW614N Brass
10. Gasket	EPDM	25. Gasket	Fiber
11. Filter	Stainless Steel	26. Nut	CW617N Brass
12. Insert	POM	27. Pipe	CW617N Brass
13. Spacer	CW617N Brass	28. O-ring	EPDM
14. Gasket	EPDM	29. Plug	Nylon
15. Disc	Stainless Steel		

Dimensions							
R	L	H	H1	H2	D	I	Kg
½"	144	151	92	59	53	82	1.0
¾"	144	151	92	59	53	82	1.0
1"	156	151	92	59	53	86	1.2

