

Stainless Steel Ball Valve - Pressfit Ends

LV 6306

Pressfit End Connections, 3 Piece CF8M Stainless Steel Body, ISO 5211 Direct Mount, Full Bore with Stainless Steel Lever and Plastic Cover.

Can be used with all tools with M-Contour; Mapress, Klauke, Rems, Rothenberger.



Pressure / Temperature Specifications

Pressure	PN16
Temperature	-35°C to 135°C

Material Specifications

1. Body	CF8M Stainless Steel	12. Handle	304 Stainless Steel
2. End	CF8M Stainless Steel	13. Cover	Plastic
3. Ball	CF8M Stainless Steel	14. Stop	304 Stainless Steel
4. Seats	PTFE	15. Washer	304 Stainless Steel
5. Stem	304 Stainless Steel	16. Nut	304 Stainless Steel
6. Gland Nut	304 Stainless Steel	17. Washer	304 Stainless Steel
7. Washer	304 Stainless Steel	18. Nut	304 Stainless Steel
8. Gland Follower	304 Stainless Steel	19. Body Bolt	304 Stainless Steel
9. Stem Packing	PTFE	20. End Cap	316 Stainless Steel
10. Thrust Washer	PTFE	21. End O-ring	EPDM
11. Stem Nut	304 Stainless Steel		

Dimensions

Size	D	L	H	h	F	A	B	C	R1	R2	H1	W
15mm	12.5	103	38.4	9	9	42	42	36	3	3	68.5	135
18mm	15	106.3	42	9	9	42	42	36	3	3	72	135
22mm	20	118	48	9	9	42	42	36	3	3	78	135
28mm	25	134.6	55	11	11	50	50	42	3.5	3	90.5	152
35mm	32	147	60	11	11	50	50	42	3.5	3	95.5	152
42mm	38	160	70	14	14	70	70	50	4.5	3.5	107	188

